



Image is for illustration purpose only



**DIESEL GENERATOR**

**FUEL OPTIMISED**

## ELECTRICAL

Frequency (Hz)	Phases	Voltage (V)	Prime		Standby		Rated Speed (RPM)
			kVA	kW	kVA	kW	
50	3	400/230V	199.0	159.0	219.0	176.0	1500
60	3	380/220V	200.0	160.0	220.0	176.0	1800
60	3	220/127V	202.4	162.0	228.1	182.5	1800
60	3	208/120V	202.4	162.0	228.1	182.5	1800

## POWER FACTOR

3 Phase	0.8
1 Phase	1

## ALL RATINGS ARE TO STANDARD REFERENCE CONDITIONS ISO 8528

**Prime:** This rating is for the supply of continuous electrical power, at variable load, in lieu of commercially purchase power. There is no limitation on the annual hours of operation and 10% over load power can be supplied for 1 hour in 12.

**Standby:** Standby Power (ESP) is the maximum output available, for up to 200 hours per year, where the average load (variable) does not exceed 70% of the standby power rating. No overload is available.

**Stage IIIA** Models are only emissions compliant at 50Hz Prime Power in accordance with 97-68EC.

## FUEL CONSUMPTION

Load Condition	Unit	Frequency	Value
100% Load Prime	L/h	50Hz	43.60
75% Load Prime	L/h		34.80
50% Load Prime	L/h		23.90
100% Load Standby	L/h		47.50
100% Load Prime	L/h	60Hz	44.60
75% Load Prime	L/h		35.30
50% Load Prime	L/h		24.70
100% Load Standby	L/h		48.80

## EXHAUST SYSTEM

Parameter	Unit	Frequency	Value
Maximum Temperature 100% Standby	°C	50Hz	508.00
Exhaust Gas Flow 100% Standby	m <sup>3</sup> /min		31.50
Maximum Allowed Back Pressure	mbar		60.00
Maximum Temperature 100% Standby	°C	60Hz	455
Exhaust Gas Flow 100% Standby	m <sup>3</sup> /min		31.14
Maximum Allowed Back Pressure	mbar		70.00

## AIR SYSTEM

Parameter	Unit	Frequency	Value
Intake Air Flow 100% Standby	Kg/h	50Hz	899.00
Total Cooling Air Flow 100% Standby (@ 16 mm H <sub>2</sub> O Canopy Depression)	m <sup>3</sup> /s		7.2
Alternator Fan Airflow	m <sup>3</sup> /s		0.53
Intake Air Flow 100% Standby	Kg/h	60Hz	1044.00
Total Cooling Air Flow 100% Standby (@ 16 mm H <sub>2</sub> O Canopy Depression)	m <sup>3</sup> /s		7.2
Alternator Fan Airflow	m <sup>3</sup> /s		0.65

## ENGINE

1500 RPM		
Gross Engine Power (PRP)	kW	187.00
Gross Engine Power (Standby)	kW	205.70
1800 RPM		
Gross Engine Power (PRP)	kW	187.00
Gross Engine Power (Standby)	kW	205.70
Manufacturer and Model		JCB 672 TA2G- 170
Fuel		Diesel
Injection		Direct
Aspiration		Turbo Charged
Cylinders		6
Bore and Stroke	mm	106 x 135
Displacement	L	7.15
Cooling		Water
Engine Oil Specification		API CH4-SAE 10W40
Compression Ratio		16.9 : 1
Engine Oil Capacity	L	28.00
Coolant Capacity	L	26.00
Governor		Electronic
Air Filter		Two stage filtration
Engine Oil Consumption	100% Load	0.1% of fuel consumed

## FUEL SYSTEM

Diesel Specification		EN590
----------------------	--	-------

## ALTERNATOR ECO38-2S4 A

Poles	4
Winding Connections	Star
Insulation	Class H
Enclosure	IP23
Exciter System	Self-regulating brushless
Voltage Regulator	AVR
Steady State Voltage Regulation	+/- 1.5%
Bearing	Single bearing sealed
Coupling	Flexible disc
Cooling	Direct drive centrifugal blower fan
Coating	Winding Protection Grey

## STARTING SYSTEM

Starter Motor	kW	4.00
Battery Capacity	Ah	110
Auxiliary Voltage	V	24

## BATTERY FEATURES

Battery Isolator	Δ
Battery Type (Optional)	Sealed Lead Acid
Battery Size (Ah)	110
Number of Batteries	2
Battery Charger	Δ
Standard: ●      Not Available: x      Optional: Δ	

## MECHANICAL FEATURES

Cooling Pack	●
Air Filter	●
Mechanical Governor	x
Low Oil Pressure Sender	●
Coolant Temperature Sender	Δ
Low Oil Pressure Sensor	Δ
Oil Temperature Sender	●
Radiator Guards	●
Hot Component Guards	Δ
Water Jacket Heater	Δ
Pre-Filter with Separator	●
Internal Fuel Fill	●
3 Way Fuel Valve with Quick Connector	Δ
Industrial Silencer	●
Bunded Base	Δ
Gravity Oil Drain Pipe	Δ
Larger Fuel Filler Neck	Δ
Electronic Governor	●
Standard: ●      Not Available: x      Optional: Δ	

## ELECTRICAL FEATURES

AVR DSR	●
AVR DER	x
Winding Protection Standard	x
Winding Protection Standard +	x
Winding Protection Grey	●
Winding Protection Total	x
Winding Protection Total +	x
MAUX	●
PMG	x
Anti-Condensation Heater	Δ
3 Pole Moulded Case Circuit Breaker	●
4 Pole Moulded Case Circuit Breaker	Δ
Earth Leakage Protection (Shunt Trip)	●
Preparation for Earth Connection	●
Optional Voltages	Δ
Synchronisation	Δ
Emergency Stop Button	●
Fuel Level Sensor	●
Standard: ●      Not Available: x      Optional: Δ	

## JCB COMMUNICATION AND CONTROL

DSE 4520	●
DSE 7320	Δ
DSE 8610	Δ
Live Link For Power	●

## CE PACK (Optional)

EMC Certification	●
Hot Guards	●
Belt Guards	●
Earth Leakage Relay	●
Sound Power Decal	●
EU Declaration for Engine Emissions	●
Complete Machine Declaration of Conformity	●
Standard: ●      Not Available: x      Optional: Δ	

## REFERENCE STANDARDS

JCB Generators are CE certified and conform to the following Directives (subject to a country requiring such standard):

- EN 12100, EN13857, EN60204
  - 2006/42/CE Machinery safety
  - 2006/95/EC Low voltage
  - 2004/108/CE Electromagnetic compatibility
  - 2000/14/EC Sound Power Level (amended by 2005/88/EC)
  - 97/68/EC Emissions(amended by 2002/88/EC & 2004/26/EC)
  - Power according to ISO 8528 and ISO 3046
  - Ambient reference conditions 1000mbar, 25°C, 30% relative humidity ISO3046
- Information based on standard specification equipment unless otherwise stated.

## WEIGHT AND DIMENSIONS – OPEN SET

Length	mm	2840
Width	mm	1030
Height	mm	1800
Shipping Volume (sea ready)	m <sup>3</sup>	5.27
Weight*	Kg	2125

*\*Standard build with all fluids except fuel*

## WEIGHT AND DIMENSIONS – CANOPY SET

Length	mm	3800
Width	mm	1140
Height	mm	2075
Shipping Volume (sea ready)	m <sup>3</sup>	9
Weight*	Kg	2700

*\*Standard build with all fluids except fuel*

## SOUND PRESSURE (CANOPY ONLY)

LpA (7m)	50Hz	dB(A)	68
----------	------	-------	----

## FUEL SYSTEM

Diesel Specification		EN590
Fuel Tank Capacity - Open	L	350
Fuel Tank Capacity - Canopy	L	360

## CANOPY FEATURES

Lockable Maintenance Access Doors	●
Control Panel Viewing Window	●
Fork Pockets	Δ
Single Lift Point	Δ
Bunding	Δ
High Density Fire Retardant Foam	●
Yellow Paint	●
White Paint	Δ
Four Point Lift (non CE)	Δ
Residential Silencer	●
Door Stops	Δ
Canopy Bump Stops	Δ
Manual Oil Drain Pump	Δ
1x32A 3 Phase / 1x16A 1 Phase Socket Box	x
1x63A 3 Phase / 3x32A 1 Phase Socket Box	x
1x63A 3 Phase / 1x32A 1 Phase / 2x16A 1Phase Socket Box	x
1x32A 3 Phase / 2x16A 1 Phase Socket Box	x
1x125A 3 Phase / 1x63A 3 Phase / 3x32A 3 Phase / 3x32A 1Phase Socket Box	Δ
External Emergency Stop Button	●

Standard: ●      Not Available: x      Optional: Δ